



Duplex Multi Mode Patch Cord

Features



- Different type of terminations SC to ST, LC to FC, etc.
- ANSI/TIA/EIA-568.B.3 compliant
- 50/125µm Multimode Riser
- 2mm, and 3mm Simplex / Duplex
- IEEE 802.3u, IEC 60794, TIA/EIA-568.B.3 compliant
- Electric interference immune
- Fibers offers low insertion loss once joined to connector
- Telcordia GR-326 tested
- Lab connectorized, each jumpers includes a quality certificate to state measuring standards

Specifications

| | | | |
|--------------------------|--|------------------|------------------|
| Norms and Standards | Telcordia GR-326, IEEE 802.3u/802.3x/802.3z/802.3j, IEC 60794, TIA/EIA-568.B.3 | | |
| Fiber Jacket | Diameter | 3mm ± 0.05mm | 2mm ± 0.05mm |
| | Thickness | 0.80mm ± 0.80mm | 0.60mm ± 0.50mm |
| Fiber optic | Temperature | -20°C up to 85°C | |
| | Core diameter | Value: ± 0.70mm | Fiber: 50/125µm, |
| | Cladding diameter | 125.0 ± 2.0µm | |
| | Core concentricity | ≤ ≤ 1.5µm | |
| | Cladding concentricity | ≤ ≤ 1.0% | |
| Wavelength | Multimode: | 850 nm | 1300 nm |
| | Maximum value | dB/Km | ≤ 3.5 |
| Recommended Light source | Multimode: | LED or VCSEL | |

Ordering Information

Example:

SV-CORD-LCULCU-MM1MD23

Starview Fiber Patchcord with LC/UPC to LC/UPC connector, Multimode 50/125um 1 meter Duplex with type 2mm, OM3 bend-insensitive fiber

| | |
|---------------------|--------------------------------|
| Manufacturer: | Starview |
| Type: | Optical Fber Patchcord |
| Connector Type #1: | SC:SC; FC:FC; ST:ST; LC:LC; |
| Polishing Grade #1: | U:UPC; A: APC |
| Connector Type #1: | SC:SC; FC:FC; ST:ST; LC:LC; |
| Polishing Grade #1: | U:UPC; A:APC |
| Fiber Type: | SM: Singlemode MM: Multimode |
| Length: | (m) 1-99 M |
| Cord Type: | S: Simplex Type D: Duplex Type |
| Cord Diameter: | (mm) 2; 3; |

